



G84

DATASHEET

CHERRY G84

HIGH PERFORMANCE RIGHT DOWN TO THE SMALLEST DETAIL!

Need a pointing device but space restrictions prevent you from using an extra mouse? The ultra-flat compact keyboard with built-in trackball is the perfect solution. The keyboard is optimally suited for 19-inch applications, slim-line PCs and laptops.



HIGHLIGHTS

- Individual keys with Gold Crosspoint contacts (ML technology)
- Designed for continuous usage - over 20 mill. confirmations per key
- High level of reliability and unique precision confirmation feeling
- Minimal space requirements
- Lightweight
- Can also be delivered without 'Windows® keys' (83 keys)
- Complete functions of a standard keyboard
- Can be used with the standard drivers of the operating system
- Ideal for 19' applications and mobile use

SCOPE OF DELIVERY

- Manual
- Keyboard

TECHNICAL DATA

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No

Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

PRODUCT VARIANTS

PART NUMBER	LAYOUT	COLOUR	SWITCHES
G84-4400	CH (Switzerland)	Black	CHERRY ML
G84-4400LPBBE-2	BE (Belgium)	Black	CHERRY ML
G84-4400LPBDE-2	DE (Germany)	Black	CHERRY ML
G84-4400LPBEU-2	EU (USA+ €-Symbol)	Black	CHERRY ML
G84-4400LPBFR-2	FR (France)	Black	CHERRY ML
G84-4400LPBGB-2	GB (United Kingdom)	Black	CHERRY ML
G84-4420LPBEU-2	US (USA)	Black	CHERRY ML
G84-4400	CH (Switzerland)	Black	CHERRY ML
G84-4400LUBBE-2	BE (Belgium)	Black	CHERRY ML
G84-4400LUBDE-2	DE (Germany)	Black	CHERRY ML
G84-4400LUBEU-2	EU (USA+ €-Symbol)	Black	CHERRY ML
G84-4400LUBFR-2	FR (France)	Black	CHERRY ML
G84-4400LUBGB-2	GB (United Kingdom)	Black	CHERRY ML
G84-4400LUBIT-2	IT (Italy)	Black	CHERRY ML
G84-4400LUBPN-2	PN (PanNordic)	Black	CHERRY ML
G84-4400LUBTQ-2	TQ (Turkey)	Black	CHERRY ML
G84-4420LUBEU-2	US (USA)	Black	CHERRY ML
G84-4400	CH (Switzerland)	Grey	CHERRY ML
G84-4400LPBDE-0	DE (Germany)	Grey	CHERRY ML
G84-4400LPBEU-0	EU (USA+ €-Symbol)	Grey	CHERRY ML

PART NUMBER	LAYOUT	COLOUR	SWITCHES
G84-4400LPBFR-0	FR (France)	Grey	CHERRY ML
G84-4400LPBGB-0	GB (United Kingdom)	Grey	CHERRY ML
G84-4400LPBRB-0	RB (US / Cyrillic)	Grey	CHERRY ML
G84-4420LPBEU-0	US (USA)	Grey	CHERRY ML
G84-4400	CH (Switzerland)	Grey	CHERRY ML
G84-4400	IT (Italy)	Grey	CHERRY ML
G84-4400	TQ (Turkey)	Grey	CHERRY ML
G84-4400LUBBE-0	BE (Belgium)	Grey	CHERRY ML
G84-4400LUBDE-0	DE (Germany)	Grey	CHERRY ML
G84-4400LUBEU-0	EU (USA+ €-Symbol)	Grey	CHERRY ML
G84-4400LUBFR-0	FR (France)	Grey	CHERRY ML
G84-4400LUBGB-0	GB (United Kingdom)	Grey	CHERRY ML
G84-4400LUBXX-0	US (USA)	Grey	CHERRY ML
G84-4420LUBEU-0	US (USA)	Grey	CHERRY ML

G84 [G84-4400]



Layout: CH (Switzerland)

Colour: Black

Switches: CHERRY ML

Part number	G84-4400
EAN	4025112062643
UPC	840183601195

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBBE-2]



Layout: BE (Belgium)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LPBBE-2
EAN	4025112062643
UPC	840183601195

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBDE-2]



Layout: DE (Germany)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LPBDE-2
EAN	4025112062667
UPC	840183601195

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBEU-2]



Layout: EU (USA+ €-Symbol)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LPBEU-2
EAN	4025112062698
UPC	840183601119

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBFR-2]



Layout: FR(France)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LPBFR-2
EAN	4025112062704
UPC	840183601195

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBGB-2]



Layout: GB (United Kingdom)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LPBGB-2
EAN	4025112062711
UPC	840183601195

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4420LPBEU-2]



Layout: US (USA)
Colour: Black
Switches: CHERRY ML

Part number	G84-4420LPBEU-2
EAN	4025112067174
UPC	840183601195

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 524 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 659 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- China RoHS - UKCA - cURus - VDE - CE - BSMI - FCC - ICES-003 (Canada)
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400]



Layout: CH (Switzerland)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400
EAN	4025112067921
UPC	840183601218

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBBE-2]



Layout: BE (Belgium)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBBE-2
EAN	4025112062841
UPC	840183601218

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBDE-2]



Layout: DE (Germany)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBDE-2
EAN	4025112062865
UPC	840183601126

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBEU-2]



Layout: EU (USA+ €-Symbol)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBEU-2
EAN	4025112062896
UPC	840183601140

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBFR-2]



Layout: FR(France)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBFR-2
EAN	4025112062902
UPC	840183601218

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBGB-2]



Layout: GB (United Kingdom)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBGB-2
EAN	4025112062919
UPC	840183601157

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBIT-2]



Layout: IT (Italy)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBIT-2
EAN	4025112062926
UPC	840183601218

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBPN-2]



Layout: PN (PanNordic)

Colour: Black

Switches: CHERRY ML

Part number	G84-4400LUBPN-2
EAN	4025112084423
UPC	840183601218

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBTQ-2]



Layout: TQ (Turkey)
Colour: Black
Switches: CHERRY ML

Part number	G84-4400LUBTQ-2
EAN	4025112075926
UPC	840183601218

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 716 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 736 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4420LUBEU-2]



Layout: US (USA)
Colour: Black
Switches: CHERRY ML

Part number	G84-4420LUBEU-2
EAN	4025112067921
UPC	840183601218

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 524 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 659 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400]



Layout: CH (Switzerland)

Colour: Grey

Switches: CHERRY ML

Part number	G84-4400
EAN	4025112067167
UPC	840183601188

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBDE-0]



Layout: DE (Germany)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LPBDE-0
EAN	4025112026386
UPC	840183601188

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBEU-0]



Layout: EU (USA+ €-Symbol)

Colour: Grey

Switches: CHERRY ML

Part number	G84-4400LPBEU-0
EAN	4025112026362
UPC	840183601102

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBFR-0]



Layout: FR(France)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LPBFR-0
EAN	4025112026867
UPC	840183601188

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBGB-0]



Layout: GB (United Kingdom)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LPBGB-0
EAN	4025112026850
UPC	840183601188

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LPBRB-0]



Layout: RB (US / Cyrillic)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LPBRB-0
EAN	4025112037856
UPC	840183601188

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- China RoHS - UKCA - cURus - VDE - CE - BSMI - ICES-003 (Canada) - FCC
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4420LPBEU-0]



Layout: US (USA)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4420LPBEU-0
EAN	4025112067167
UPC	840183601188

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 524 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 659 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- China RoHS - UKCA - cURus - VDE - CE - BSMI - FCC - ICES-003 (Canada)
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400]



Layout: CH (Switzerland)

Colour: Grey

Switches: CHERRY ML

Part number	G84-4400
EAN	4025112060380
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400]



Layout: IT (Italy)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400
EAN	4025112060380
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400]



Layout: TQ (Turkey)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400
EAN	4025112060380
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBBE-0]



Layout: BE (Belgium)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LUBBE-0
EAN	4025112049330
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBDE-0]



Layout: DE (Germany)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LUBDE-0
EAN	4025112026881
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBEU-0]



Layout: EU (USA+ €-Symbol)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LUBEU-0
EAN	4025112037849
UPC	840183601133

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBFR-0]



Layout: FR(France)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LUBFR-0
EAN	4025112026904
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBGB-0]



Layout: GB (United Kingdom)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LUBGB-0
EAN	4025112026898
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4400LUBXX-0]



Layout: US (USA)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4400LUBXX-0
EAN	4025112060380
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 531 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 668 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4420LUBEU-0]



Layout: US (USA)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4420LUBEU-0
EAN	4025112067914
UPC	840183601201

PRODUCT INFORMATION

Dimensions and weight (without packaging)	370 mm × 139 mm × 19.6 mm 524 g
Dimensions and weight (including packaging)	385 mm × 195 mm × 30 mm 659 g
Model number	ML4400
Warranty	2 years warranty
Product approvals	- BSMI - RCM - CE - cURus - FCC - ICES-003 (Canada) - UKCA - VCCI - VDE
Software support	CHERRY KEYS
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	40 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Max. current consumption (mA) of keyboard	24 mA
Keyboard format	Compact (75%)
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

© Cherry Europe GmbH
Cherrystraße 2 · 91275 Auerbach/OPf. · Germany
cherry-world.com · cherry.de

Sales Support · Technischer Support · eHealth Support
+49 9643 - 2061 - 100
www.cherry.de/de-de/kontakt

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products.