




G84

CHERRY G84

INDIVIDUALLY PROGRAMMABLE KEYS!

Whether for numerical inputs, controls or for frequent number entry - the keyboard is the ideal accessory for notebooks. All keys can be user-defined via software macros.



HIGHLIGHTS

- Complete layout with numeric keypad. Ideal for applications requiring the frequent input of figures
- High degree of reliability and precise keystroke feel thanks to individual keys with Gold Crosspoint contacts (CHERRY ML technology)
- Ideal for continuous usage due to the long operating life in excess of 20 million key confirmations per individual key
- Compact dimensions and very low overall build height, ideal for restricted spaces and for 19" applications
- Lightweight - for applications where every gram counts
- Plug & Play - can be used with the operating system's standard drivers
- Supports Code Set 3 and UnifiedPOS
- User-defined via software macros for even more time-saving operation

SCOPE OF DELIVERY

- Manual
- Keyboard

TECHNICAL DATA

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- cURus - BSMI - VDE - VCCI - UKCA - CE - RCM - ICES-003 (Canada) - FCC
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	50 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no

Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

PRODUCT VARIANTS

PART NUMBER	LAYOUT	COLOUR	SWITCHES
G84-4700LPBUS-2	US (USA)	Black	CHERRY ML
G84-4700LUCDE-2	DE (Germany)	Black	CHERRY ML
G84-4700LUCES-2	ES (Spain)	Black	CHERRY ML
G84-4700LUCFR-2	FR (France)	Black	CHERRY ML
G84-4700LUCUS-2	US (USA)	Black	CHERRY ML
G84-4700LPBDE-0	DE (Germany)	Grey	CHERRY ML
G84-4700LPBFR-0	FR (France)	Grey	CHERRY ML
G84-4700LPBUS-0	US (USA)	Grey	CHERRY ML
G84-4700LUCDE-0	DE (Germany)	Grey	CHERRY ML
G84-4700LUCFR-0	FR (France)	Grey	CHERRY ML
G84-4700LUCUS-0	US (USA)	Grey	CHERRY ML

G84 [G84-4700LPBUS-2]



Layout: US (USA)
Colour: Black
Switches: CHERRY ML

Part number	G84-4700LPBUS-2
EAN	4025112061448
UPC	840183601249

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- CE - cULus - FCC - VDE
Operating system	Windows
System Requirements-Hardware	PS/2

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	50 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LUCDE-2]



Layout: DE (Germany)

Colour: Black

Switches: CHERRY ML

Part number	G84-4700LUCDE-2
EAN	4025112063015
UPC	840183601263

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- BSMI - RCM - CE - cULus - FCC - VCCI - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	50 °C
----------------------------	-------

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LUCES-2]



Layout: ES (Spain)
Colour: Black
Switches: CHERRY ML

Part number	G84-4700LUCES-2
EAN	4025112063039
UPC	840183601263

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- BSMI - RCM - CE - cULus - FCC - VCCI - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	50 °C
----------------------------	-------

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LUCFR-2]



Layout: FR(France)
Colour: Black
Switches: CHERRY ML

Part number	G84-4700LUCFR-2
EAN	4025112063046
UPC	840183601263

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- BSMI - RCM - CE - cULus - FCC - VCCI - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	50 °C
----------------------------	-------

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LUCUS-2]



Layout: US (USA)
Colour: Black
Switches: CHERRY ML

Part number	G84-4700LUCUS-2
EAN	4025112063053
UPC	840183601263

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- BSMI - RCM - CE - cULus - FCC - VCCI - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	50 °C
----------------------------	-------

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LPBDE-0]



Layout: DE (Germany)

Colour: Grey

Switches: CHERRY ML

Part number	G84-4700LPBDE-0
EAN	4025112027215
UPC	840183601232

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- CE - cULus - FCC - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	50 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LPBFR-0]



Layout: FR(France)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4700LPBFR-0
EAN	4025112027239
UPC	840183601232

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- CE - cULus - FCC - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	50 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LPBUS-0]



Layout: US (USA)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4700LPBUS-0
EAN	4025112027208
UPC	840183601232

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- CE - cULus - FCC - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
Max. operating temperature	50 °C

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LUCDE-0]



Layout: DE (Germany)

Colour: Grey

Switches: CHERRY ML

Part number	G84-4700LUCDE-0
EAN	4025112043390
UPC	840183601256

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- BSMI - RCM - CE - cULus - FCC - VCCI - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	50 °C
----------------------------	-------

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LUCFR-0]



Layout: FR(France)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4700LUCFR-0
EAN	4025112043949
UPC	840183601256

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- BSMI - RCM - CE - cULus - FCC - VCCI - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	50 °C
----------------------------	-------

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

G84 [G84-4700LUCUS-0]



Layout: US (USA)
Colour: Grey
Switches: CHERRY ML

Part number	G84-4700LUCUS-0
EAN	4025112043222
UPC	840183601256

PRODUCT INFORMATION

Dimensions and weight (without packaging)	90 mm × 132 mm × 36 mm 186 g
Dimensions and weight (including packaging)	185 mm × 140 mm × 45 mm 239 g
Model number	G84-4700
Warranty	2-year statutory warranty + 1-year manufacturer's warranty
Product approvals	- BSMI - RCM - CE - cULus - FCC - VCCI - VDE
Operating system	Windows
System Requirements-Hardware	USB-A

TEMPERATURE

Min. operating temperature	0 °C
----------------------------	------

Max. operating temperature	50 °C
----------------------------	-------

KEYBOARD

Keycap material	ABS
USB-Hub	no
Illumination	No
Status LEDs	no
Max. current consumption (mA) of keyboard	5 mA
Keyboard format	Num pad
Integrated metal plate	no
N-Key Rollover	no
Anti-ghosting	no

SWITCHES: CHERRY ML



LAYOUT

RGB	no
Cover colour	Black
Bottom housing colour	Black
Actuation force	45 cN
Initial force	30 cN

© Cherry Europe GmbH

Cherrystraße 2 · 91275 Auerbach/OPf. · Germany

cherry-world.com · cherry.de

Sales Support · Technischer Support · eHealth Support

+49 9643 - 2061 - 100

www.cherry.de/de-de/kontakt

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products.