






LED Rückfahr-, LED Manövrierscheinwerfer

LED Reversing Lamp, LED Manoeuvring Lamp



Typ: PRO-FIELD, PRO-REVERSE II, PRO-REVERSE-WALL

Artikel-Nr. *Reference-No.*	**VE** *QTY*	**Beschreibung** *Description*	**LED Leuchten** *LED Lamps*	**LED Technik** *LED Technology*
40 424 003	1	LED Rückfahrscheinwerfer PRO-FIELD, geprüft gem. ECE R23, 800lm, sehr homogene Ausleuchtung, 12W, Kabel 0,45m, ADR gepr. IP54, R10, IP67, 9-32V *LED Reversing-Work Lamp PRO-FIELD, according to ECE R23, 800 lumen, homogeneous illumination, 12W, cable 0,45m, ADR appr. IP54, R10, IP67, 9-32V*	**800lm** 	
40 424 603	1	LED Manövrierscheinwerfer PRO-FIELD ML, **ECE R23 ML** *LED Manoeuvring Lamp PRO-FIELD ML **ECE R23 ML***		
40 474 003	1	LED Rückfahrscheinwerfer PRO-REVERSE II, geprüft gem. ECE R23, 1500lm, sehr homogene Ausleuchtung, 18W, Kabel 0,5m, ADR & EMV geprüft, IP6K9K, 9-32V *LED Reversing-Work Lamp PRO-REVERSE II, according to ECE R23, 1500 lumen, homogeneous illumination, 18W, cable 0,45m, ADR & EMC appr., IP6K9K, 9-32V*	**1500lm** 	
40 474 603	1	LED Manövrierscheinwerfer PRO-REVERSE ML, **ECE R23 ML** *LED Manoeuvring Lamp PRO-REVERSE ML **ECE R23 ML***		
40 066 903	1	LED Rückfahr-/Umfeldleuchte PRO-REVERSE-WALL, geprüft gemäß ECE R23, Aluminium-Druckgussgehäuse, Lichtscheibe aus PC, Kabel 3,0m, 1100 Lumen Rückfahrleuchte, 3000 Lumen Umfeldleuchte, EMV, CISPR Class 4 & SAE J595 geprüft, 10-30V, ADR (in Vorbereitung) IP6K9K *comb. LED Reversing Lamp / Scenelite PRO-REVERSE-WALL according to ECE R23, Aluminium die casted, Lens made of PC, cable 3,0m, 1100 Lumen Reverse, 3000 Lumen Scenelite, EMC approved, CISPR Class 4 & SAE J595 approved, 10-30V, ADR (pending) IP6K9K*	**3000lm**   	  
40 066 994	1	Abdeckung PRO-REVERSE-WALL *Cover PRO-REVERSE-WALL*		

LED Manövrierscheinwerfer

LED Manoeuvring Lamp

Typ: PRO-REVERSE ML, PRO-FIELD ML

Artikel-Nr. *Reference-No.*	VE *QTY*	Beschreibung *Description*	LED Manövrierscheinwerfer *LED Manoeuvering Lamps*	LED Technik *LED Technology*
40 474 603	1	LED Manövrierscheinwerfer PRO-REVERSE ML, geprüft gem. **ECE R23 ML**, ca. 1500lm, sehr homogene Ausleuchtung, 18W, Kabel 0,5m, IP6K9K, EMV geprüft, 9-32V *LED Manoeuvring Lamp PRO-REVERSE ML, according to **ECE R23 ML**, 1500 lumen, homogeneous illumination, 18W, cable 0,5m, IP6K9K, EMC appr., 9-32V*	**1500lm** 	 
40 424 603	1	LED Manövrierscheinwerfer PRO-FIELD ML, geprüft gem. **ECE R23 ML**, 800lm, sehr homogene Ausleuchtung, 12W, Kabel 0,45m, IP67, EMV geprüft, 9-32V *LED Manoeuvring Lamp PRO-FIELD ML, according to **ECE R23 ML**, 800 lumen, homogeneous illumination, 12W, cable 0,45m, IP67 & EMC appr., 9-32V*	**800lm** 	